



*Filocomando a richiesta
Remote cable control
on request*



))) 100 m

*Radiocomando
a richiesta
Radio control
on request*

Modello Type	Alimentazione Feeding		kW	Giri/min. RPM	Hz	H = Prevalenza (metri) / Head (meters) - Q = Portata (litri/minuto) / Capacity (liters/minute)																											
						0	2	4	5	6	8	10	12	14	15	18	20	22	24	30	35	40	45	55	60	H							
INV NEOS 3/4"	TF* 400V 50Hz	MF* 230V 50Hz	0.25	1200	20	10	0																										
				1400	25	14	10	3	0																								
				1800	30	18	14	8	5	0																							
				2240	40	26	24	21	20	18	14	10	5	0																			
				2800	50	29	27	26	25	24	22	18	16	14	13	8	4	0															
				3300	60	36	34	32	31	30	27	25	22	19	17	12	8	4	0														
INV JUNIOR 1"1/4	TF* 400V 50Hz	MF* 230V 50Hz	0.56	1200	20	13	0																										
				1400	25	17	10	0																									
				1800	30	22	16	6	0																								
				2240	40	45	39	33	30	26	19	10	0																				
				2800	50	58	54	50	47	45	40	35	30	25	22	13	7	0															
				3300	60	62	58	54	52	50	45	40	35	30	27	19	13	7	0														
INV SENIOR 1"1/2	TF* 400V 50Hz	MF* 230V 50Hz	1.1	600	20	50	35	0																									
				900	30	75	63	50	40	30	0																						
				1120	40	100	90	76	70	62	48	30	0																				
				1400	50	120	115	110	105	100	95	85	80	68	62	45	30	0															
				1700	60	150	142	135	130	125	115	107	95	85	80	60	40	25	0														
INV MASTER 2"	TF* 400V 50Hz	MF* 230V 50Hz	1.85	600	20	90	55	0																									
				900	30	140	125	105	95	85	65	40	0																				
				1120	40	185	170	160	150	145	130	110	90	70	60	25	0																
				1400	50	230	220	210	205	200	185	175	160	145	140	120	95	80	60	0													
				1700	60	250	240	230	225	220	210	200	185	170	165	145	130	115	100	45	0												
INV EP 60 Inox	TF* 400V 50Hz		4.0	600	20	125	80	30	0																								
				900	30	185	160	140	125	115	85	60	30	0																			
				1120	40	265	245	230	220	210	190	170	145	125	110	75	50	25	0														
				1400	50	350	335	320	310	300	285	265	250	230	220	190	170	150	130	60	0												
				1700	60	385	370	355	350	340	325	310	290	270	265	240	220	200	180	120	60	0											
INV 70 Inox	TF* 400V 50Hz		7.5	600	20	215	180	140	115	85	0																						
				900	30	320	290	260	245	230	190	150	100	40	0																		
				1120	40	420	400	375	360	350	325	295	265	230	215	160	110	60	0														
				1400	50	500	480	460	455	450	430	415	390	370	365	330	300	280	255	165	90	0											
				1700	60	570	550	535	530	520	500	490	465	455	440	400	380	360	340	260	190	100	0										
INV 80 Inox	TF* 400V 50Hz		15	600	20	360	310	240	200	160	0																						
				900	30	540	500	470	450	430	390	340	290	230	200	100	0																
				1120	40	710	680	655	640	630	600	565	535	500	485	430	390	350	310	160	0												
				1400	50	900	880	850	840	830	800	780	750	730	720	660	650	620	580	500	410	310	220	0									
				1700	60	970	945	920	910	890	870	850	810	790	770	730	690	670	640	540	470	380	290	100	0								

* TF = trifase - MF = monofase / TF = three phase - MF = single phase

